

- Design ultramodern
- Display digital cu cristale lichide VFD si telecomanda wireless
- Compressoare scroll
- Rezistenta electrica suplimentara incorporata
- Debit mare de aer
- Functie auto restart
- Functionare silentioasa
- Eficienta ridicata, consum de energie electrica redus
- Jaluzele verticale automate cu min. 10 pozitii
- Capacitate de functionare la temperaturi de la -15 grade C pana la +52 grade C



CARACTERISITICI TEHNICE

Model	CSRC24LW		CSRC42LW		CSRC55LW	
Mod de functionare	Racire	Incalzire	Racire	Incalzire	Racire	Incalzire
Capacitate (Btu/h)	24000	26000	42000	44000	55000	58000
Capacitate incalzire rezistenta electrica suplimentara (W)		1500		3500		3500
Capacitate dezumidificare (l/h)	2,8		5,0		4,5	
Consum electric	3200	2600	5300	4700	6150	5800
E.E.R./C.O.P. (W/W)	2,2	2,2	2,7	2,7	2,85	3,4
Alimentare electrica	1Ph, 220-240V, 50Hz		3Ph, 380-415V, 50Hz		3Ph, 380-415V, 50Hz	
Unitate interioara						
Dimensiuni (mm)	500x1710x300		540x1790x380		580x1850x380	
Greutate bruta/neta (kg)	43/65		58/72		60/85	
Nivel zgomot (dB(A))	46		53		58	
Debit aer (m3/h)	900		1600		2050	
Unitate exterioara						
Dimensiuni (mm)	1018x840x412		1032x1250x412		1032x1250x412	
Greutate bruta/neta (kg)	71/77		112/123		112/123	
Nivel zgomot (dB(A))	56		61		64	
Alte caracteristici						
Diametru teava lichid	3/8"		1/2"		1/2"	
Diametru teava gaz	5/8"		3/4"		3/4"	
Refrigerant	R407C (2,4 kg)		R407C (3,8 kg)		R407C (5,5 kg)	

