



GCV 803624D A04 TS2R ANTICALC

Modelele verticale Base Line/ ANTICALC

Aparate de incalzire





Termostat reglabil



Anod de protectie



Izolatie termica de
inalta eficienta



Informatii principale

- Protectie sigura impotriva coroziunii
- Depunere redusa de calcar
- Termen de viata sporit
- Proces de incalzire silentios
- Intrerupator in doua trepte - ofera posibilitatea alegerii intre incalzire rapida si incalzire normala
- Element de incalzire din otel inoxidabil foarte rezistent - protejat cu un manson ceramic
- Nivel ridicat de siguranta - nu exista contact intre elementul de incalzire si apa
- Intretinere simpla si rapida
- Service convenabil - nu este necesara evacuarea apei din boiler pentru schimbarea elementului electric
- Protectie cu sticla-ceramica a vasului
- Termostat reglabil
- Anod de magneziu cu 3 ani durata de folosire
- Flansa
- Termoizolatie de inalta eficienta
- Protectie anti-inghet



Caracteristici tehnice	
Volum [L]	80 L
Protectia vasului	Sticla ceramica
Tensiunea de alimentare [V/Hz]	230V/50Hz
Putere nominala [W]	2000 W
Trepte de putere [W]	2400 W / 1200 W
Presiunea de lucru [Mpa]	0.8 MPa
Izolatie [mm]	18 mm
Timpul de incalzire de la 15°C la 65°C	1h 56 min / 3h 52 min
Intrerupator cu doua trepte rezistent la umiditate	Da
Termostat reglabil	Da
Anod de magneziu	Da
Anod tester	Nu
Supapa de siguranta	Da
Dimensiuni H/ l/ D [m]	1.130 x 0.350 x 0.370 m
Greutate neta [kg]	23.9 kg
Instalare	Vertical