



GCV 8047 20 P62 E

Premium Line cu control electronic



Informatii principale

Protectie cu sticla-ceramica

Termostat electronic de precizie

Termometru digital

Anod de magneziu

Izolatie termica eficienta de poliuretan rigid de inalta densitate cu 32 mm grosime garanteaza o pierdere minima de caldura si reducerea consumului de energie.

Iesirea apei calde din otel inoxidabil


Intrarea apei reci printr-un difuzor

Flansa permite o mentenanta facila a boilerului

Supapa de siguranta



Interrupator On/Off



Anod tester



Termostat reglabil



GCV 8047 20 P62 E

Premium Line cu control electronic

Caracteristici tehnice	
Volum [L]	80 L
Protectia vasului	Sticla ceramica
Tensiune de alimentare [V/Hz]	230V/50Hz
Putere nominala [W]	2000 W
Presiunea de lucru [Mpa]	0.8 MPa
Izolatie [mm]	32 mm
Timpul de incalzire de la 15°C la 65°C	2 h 20 min
Intrerupator On/ Off	Da
Termostat electronic	Da
Anod de magneziu	Da
Anod tester	Da
Supapa de siguranta	Da
Dimensiuni H/ l/ D [m]	0.776 x 0.470 x 0.490 m
Greutate neta [kg]	22.40 kg
Instalare	Vertical
Garantie	n/a